



Introduction to High Speed Airbreathing Propulsion Systems



KR/LH02072001

About the Rocket Motor?



- **Propellants combine and burn in combustion chamber**

- Oxidizer ... “liquid air”
Have to take our own along
So that the engine can breathe
At high altitudes

- How Much Oxidizer?
... depending on chosen propellants
... 4-9 times as much
As the fuel we carry!

Flight Without Oxidizer, I

What if we could get enough oxygen from ambient air?




What happens to our I_{sp} ?


$$I_{sp} = \frac{F}{g_o \dot{m}} = \frac{F}{g_o [\dot{m}_{fuel} + \dot{m}_{ox}]} \approx \frac{F}{g_o [\dot{m}_{fuel} + 6 \dot{m}_{fuel}]} = \textcircled{7} g_o [\dot{m}_{fuel}]$$

OK .. Lets loose the Oxidizer ... and our I_{sp} goes up by a factor Of 7! ... but where do we the the Oxidizer for combustion?

POTENTIAL AIR-BREATHING HYPERSONONIC VEHICLE APPLICATIONS AND THEIR FLIGHT ENVELOPES



Flight Without Oxidizer, II




Fuel Efficiencies of Various High Speed Propulsion Systems

Turbojet



- Uses atmospheric air
- Complex turbomachinery
- Subsonic combustion
- Mach range: 0 to 3


Propulsion systems comparison



Ramjet



- Uses atmospheric air
- "Ram" compression → no turbomachinery
- Subsonic combustion
- Mach range: 2 to 6



Rocket



- Carries oxidizer
- No turbomachinery
- Subsonic combustion
- Mach range: 0 to 25

Scramjets have the highest efficiency above Mach 6


Minimal turbo-machinery

Scramjet



- Uses atmospheric air
- "Ram" compression → no turbomachinery
- Supersonic combustion
- Mach range: 5 to ~25

Operational Flight Envelope for Various Flight Vehicles



Operations Payoffs for Airbreathing Launch

- Decreased gross lift-off weight, resulting in smaller facilities and easier handling
- Wider range of emergency landing sites for intact abort
- Powered flyback/go-around & more margin at reduced power
- Self-ferry & taxi capabilities
- Greatly expanded launch windows (double or triple)
- Rapid orbital rendezvous (up to three times faster than rockets)
- Wider array of landing sites from orbit, with 2,000-mile cross range and increased range
- Reduced sensitivity to weight growth


Applications

Space Access



RLV (Affordable, timely
access to space)

Weapons



Hypersonic Cruiser
(Global Reach/Attack)


Hypersonic Missile
(Time-critical targets)

Far-Term


Mid-Term

Near-Term

**Pursue
Stepping-
Stone
Approach**




Airbreathing Propulsion Basics



Airbreathing Propulsion Basics (cont'd)


- Turbojet/Turbo fan engines Combustion Cycle steps

Compression and
Power extraction
steps use
Turbo-machinery
To augment cycle



Airbreathing Propulsion Basics (cont'd)


turbojet. Simple turbine engine that produces all of its thrust from the exhaust from the turbine section. However, because all of the air is passing through the whole turbine, all of it must burn fuel.



Airbreathing Propulsion Basics (cont'd)

Turbofan. Turbine primarily drives a fan at the front of the engine. Most engines drive the fan directly from the turbine. Part of the air enters the turbine section of the engine, and the rest is bypassed around the engine. In high-bypass engines, most of the air only goes through the fan and bypasses the rest of the engine and providing most of the thrust.


A turbofan thus can be thought of as a turbojet being used to drive a ducted fan, with both of those contributing to the thrust. The ratio of the mass-flow of air bypassing the engine core compared to the mass-flow of air passing through the core is referred to as the [bypass ratio](#).



Airbreathing Propulsion Basics (cont'd)



Turbofans have a number of benefits over simple turbojets. It is more energy efficient to accelerate a large air mass by a small amount, than a small air mass by a lot. A turbofan effectively increases the volume of air propelled with a corresponding decrease in average exhaust gas velocity.

Larger, slower fan, positioned upwind of the compressor pushes air (relatively) slowly through both the core and the bypass. The air that makes it to the core is compressed and undergoes combustion. The air that makes it to the bypass is ducted around the core, and mixes with the exhaust gases when it exits the back of the engine.



Airbreathing (Jet) Propulsion Basics (cont'd)

- Ramjet Engine




- Simplest of all Jet Engine= Concepts

- Compression and Power Extraction steps Performed passively

- Requires High Speed inlet flow to operate

Airbreathing (Jet) Propulsion Basics (cont'd)


- Ramjet Engine



Ramjets cannot produce thrust at zero airspeed; they cannot move an aircraft from a standstill. A ramjet powered vehicle, therefore, requires an assisted take-off like a rocket assist to accelerate it to a speed where it begins to produce thrust.

<https://www.youtube.com/watch?v=1DG4f2umclk>



Ideal Ramjet Cycle Analysis



Region	Process	Ideal Behavior	Real Behavior
A to 1(inlet)	Isentropic flow	P_o, T_o constant	P_o drop
1-2 (diffuser)	Adiabatic Compression	P, T increase P_o drop	P_o drop
2-3 (burner)	Heat Addition	P_o constant, T_o s Increase $\Delta s = \left(\frac{\Delta q}{T} \right)_{rev} > 0$	P_o drop
3-4 (nozzle)	Isentropic expansion	T_o, P_o constant $\Delta s > \Delta s_{rev}$	s Increase T_o drop


Ideal Ramjet Cycle Analysis

T-s Diagram



Thermodynamic Efficiency of Ideal Ramjet

- Net Work Available --> work perform by system in step 4 minus work required for step 1-2
- Net heat input --> heat input during step 3 (combustion)
 - heat lost in exhaust plume




Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- Ideal Cycle Efficiency(η) = (Net work output)/(Net heat input}

$$\frac{\dot{Net\ Work}}{\dot{m}} = (h_A - h_B) + (h_C - h_D)$$


$$\frac{\dot{Net\ Heat\ Input}}{\dot{m}} = (h_C - h_B)$$



Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- Ideal Cycle Efficiency = (Net work output)/(Net heat input}


$$\eta = \frac{\left(\frac{\dot{Net\ Work}}{\dot{m}} \right)}{\left(\frac{\dot{Net\ Heat\ Input}}{\dot{m}} \right)} = \frac{(h_A - h_B) + (h_C - h_D)}{(h_C - h_B)} = 1 - \frac{(h_D - h_A)}{(h_C - h_B)}$$



Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- Assume ... $C_{p_{air}} \sim C_{p_{products}}$

$$\eta = 1 - \frac{\left(C_{p_{products}} T_D - C_{p_{air}} T_A \right)}{\left(C_{p_{air}} T_C - C_{p_{products}} T_B \right)} = 1 - \frac{\left(T_D - \frac{C_{p_{air}}}{C_{p_{products}}} T_A \right)}{\left(\frac{C_{p_{air}}}{C_{p_{products}}} T_C - T_B \right)}$$



Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- For simplicity ... let ... $C_{p_{air}} \sim C_{p_{products}}$

$$\eta \approx 1 - \frac{\left(T_D - \frac{C_{p_{air}}}{C_{p_{products}}} T_A \right)}{\left(\frac{C_{p_{air}}}{C_{p_{products}}} T_C - T_B \right)} = 1 - \frac{(T_D - T_A)}{(T_C - T_B)}$$


$$= 1 - \frac{\left(\frac{T_D}{T_C} - \frac{T_A}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)} = 1 - \frac{\left(\frac{T_D}{T_C} - \frac{T_A}{T_B} \frac{T_B}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)}$$



Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- From C-->D flow is isentropic ...


$$\rightarrow \frac{T_D}{T_C} = \left(\frac{P_D}{P_C} \right)^{\frac{\gamma-1}{\gamma}}$$



$$\eta = 1 - \frac{\left(\frac{T_D}{T_C} - \frac{T_A}{T_B} \frac{T_B}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)} = 1 - \frac{\left(\left(\frac{P_D}{P_C} \right)^{\frac{\gamma-1}{\gamma}} - \frac{T_A}{T_B} \frac{T_B}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)}$$

Thermodynamic Efficiency of Ideal Ramjet (cont'd)

- Adiabatic compression across diffuser




$$\left(\frac{P_A}{P_B} \right) = \left(\frac{P_A}{P_{0A}} \times \frac{P_{0A}}{P_{0B}} \times \frac{P_{0B}}{P_B} \right) =$$

$$\left(\frac{T_A}{T_{0A}} \right)^{\frac{\gamma}{\gamma-1}} \left(\frac{T_{0B}}{T_B} \right)^{\frac{\gamma}{\gamma-1}} \frac{P_{0A}}{P_{0B}} \rightarrow T_{0A} = T_{0B} \rightarrow \frac{T_A}{T_B} = \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \left(\frac{P_{0B}}{P_{0A}} \right)^{\frac{\gamma-1}{\gamma}}$$

Thermodynamic Efficiency of Ideal Ramjet (cont'd)


- Sub into efficiency equation



$$\eta = 1 - \frac{\left(\left(\frac{P_D}{P_C} \right)^{\frac{\gamma-1}{\gamma}} - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \left(\frac{P_{0B}}{P_{0A}} \right)^{\frac{\gamma-1}{\gamma}} \frac{T_B}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)}$$

Thermodynamic Efficiency of Ideal Ramjet (cont'd)


ideal nozzle $\rightarrow P_A = P_D$
ideal burner $\rightarrow P_B = P_C$



$$\eta = 1 - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \frac{\left(1 - \left(\frac{P_{0_B}}{P_{0_A}} \right)^{\frac{\gamma-1}{\gamma}} \frac{T_B}{T_C} \right)}{\left(1 - \frac{T_B}{T_C} \right)} = 1 - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \frac{\left(T_C - \left(\frac{P_{0_B}}{P_{0_A}} \right)^{\frac{\gamma-1}{\gamma}} T_B \right)}{(T_C - T_B)}$$

Thermodynamic Efficiency of Ideal Ramjet (cont'd)

$$\eta = 1 - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \frac{\left(T_C - \left(\frac{P_{0_B}}{P_{0_A}} \right)^{\frac{\gamma-1}{\gamma}} T_B \right)}{(T_C - T_B)}$$




- i) As engine pressure ratio, P_B/P_A , goes up ... η goes up
- ii) As combustor temperature difference $T_C - T_B$ goes up ... η goes up
- iii) As inlet total pressure ratio (P_{0_B}/P_{0_A}) goes down ... (stagnation pressure loss goes up) ... η goes down

Why is total pressure recovery important?

- Choked Nozzle Throat massflow

$$\frac{\dot{m}}{A^*} = \sqrt{\frac{\gamma}{R_g} \left(\frac{2}{\gamma + 1} \right)^{\frac{\gamma+1}{(\gamma-1)}} \frac{p_0}{\sqrt{T_0}}}$$



- Thrust is proportional to engine massflow



$$Thrust = \dot{m}_e V_e - \dot{m}_i V_i + (p_e A_e - p_\infty A_e)$$


Ideal Ramjet: *Inlet and Diffuser*

- Take a Rocket motor and “lop the top off”



- Works Ok for subsonic, but for supersonic flow ... can't cram enough air down the tube
- Result is a *normal shock wave* at the inlet lip


Ideal Ramjet: *Inlet and Diffuser (cont'd)*



- Mechanical Energy is Dissipated into Heat
- Huge Loss in Momentum


Ideal Ramjet: *Inlet and Diffuser (cont'd)*

- So ... we put a spike in front of the inlet




- How does this spike Help?
- By forming an Oblique Shock wave ahead of the inlet

2-D Ramjet Inlet Example




2-D Ramjet Inlet Example (cont'd)



- From Normal Shock wave solver

$$M_{\infty} \xrightarrow{\text{normal...shock}} M_B = 0.434959 \Rightarrow \begin{bmatrix} \frac{P_{0B}}{P_{0\infty}} = 0.1388 \\ \frac{p_B}{p_{\infty}} = 18.5 \end{bmatrix}$$

2-D Ramjet Inlet Example (cont'd)




- Across Oblique Shock wave

- $M_{1n} = M_1 \sin \beta_1 = 4 \sin \left(\frac{\pi}{180} 40 \right) = 2.571 \longrightarrow M_{2n} = 0.5064$

$$\tan(\theta) = \frac{2 \{ M_1^2 \sin^2(\beta) - 1 \}}{\tan(\beta) [2 + M_1^2 [\gamma + \cos(2\beta)]]} \rightarrow \frac{180}{\pi} \operatorname{atan} \left(\frac{2 \left(4^2 \sin^2 \left(\frac{\pi}{180} 40 \right) - 1 \right)}{\left(\tan \left(\frac{\pi}{180} 40 \right) \right) \left(2 + 4^2 \left(1.4 + \cos \left(\frac{\pi}{180} 2 \cdot 40 \right) \right) \right)} \right)$$

$$\theta = 26.2^\circ$$

2-D Ramjet Inlet Example (cont'd)




- Across Oblique Shock wave

$$M_2 n = 0.5064 \rightarrow M_2 = \frac{M_2 n}{\sin(\beta_1 - \theta)} = \frac{0.5064}{\sin\left(\frac{\pi}{180} (40 - 26.2)\right)} = 2.123$$

$$P_{02}/P_{01} = 0.4711$$

2-D Ramjet Inlet Example (cont'd)




- Across Normal Shock wave (*behind oblique Shock*)

$$M_2 = 2.123 \xrightarrow{\text{normal..shock}} M_B = 0.557853 \Rightarrow$$


$$\frac{P_{0_B}}{P_{0_2}} = 0.663531 \Rightarrow \frac{P_{0_B}}{P_{0_\infty}} = \frac{P_{0_B}}{P_{0_2}} \frac{P_{0_2}}{P_{0_\infty}} = (0.663531)(0.4711) = 0.3126$$

$$\frac{p_B}{p_\infty} = \frac{p_B}{P_{0_B}} \times \frac{P_{0_B}}{P_{0_\infty}} \times \frac{P_{0_\infty}}{p_\infty} = \frac{0.3126 \left(\left(1 + \frac{1.4-1}{2} 4^2 \right)^{\frac{1.4}{(1.4-1)}} \right)}{\left(\left(1 + \frac{1.4-1}{2} 0.557853^2 \right)^{\frac{1.4}{(1.4-1)}} \right)} = 38.422$$

2-D Ramjet Inlet Example (cont'd)



- Compare
 - Spike aids in increasing Total Pressure recovery
 - Reducing “ram drag”



2-D Ramjet Inlet Example (cont'd)

- ... Continuing example ... **Incoming Air to Ramjet**
- Molecular weight = 28.96443 kg/kg-mole
- γ = 1.40
- R_g = 287.056 J/°K-(kg)
- T_∞ = 216.65 °K
- p_∞ = 19.330 kPa
- Combustor $q = q/m = 500$ kJ/kg
- *Assume that mass of added fuel is negligible, exhaust and γ , R_g are the same*


2-D Ramjet Inlet Example (cont'd)

- Compute free stream stagnation temperature

$$T_{0_\infty} = T_\infty \left[1 + \frac{\gamma - 1}{2} M_\infty^2 \right] = 216.65 \left(1 + \frac{1.4 - 1}{2} 4^2 \right) = 909.93^\circ\text{K}$$


- Compute BURNER stagnation temperature

$$T_{0_c} = \frac{q + c_p T_{0_\infty}}{c_p} = \frac{500 \cdot 10^3 + 1004.696 (909.93)}{1004.696} = 1407.6^\circ\text{K}$$



2-D Ramjet Inlet Example (cont'd)

- Compute efficiency Normal shock inlet




- Compute T_C , T_B

$$T_{C_B} = \frac{909.93}{\left(1 + \frac{1.4 - 1}{2} 0.435^2\right)} = 867.75^\circ\text{K}$$

$$T_{B_C} = \frac{1407.6}{\left(1 + \frac{1.4 - 1}{2} 0.435^2\right)} = 1356.3^\circ\text{K}$$

2-D Ramjet Inlet Example (cont'd)

- Compute efficiency Normal shock inlet



- Compute T_C , T_B

$$T_{C_B} = 867.75^\circ\text{K}$$


$$T_{B_C} = 1356.3^\circ\text{K}$$

$$\eta = 1 - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \frac{\left(T_C - \left(\frac{P_{0_B}}{P_{0_A}} \right)^{\frac{\gamma-1}{\gamma}} T_B \right)}{(T_C - T_B)} =$$

$$1 - \frac{18.5^{-\frac{(1.4-1)}{1.4}} \left(1356.3 - \left(0.1388^{\frac{(1.4-1)}{1.4}} \right) 867.75 \right)}{(1356.3 - 867.75)} = 0.2328$$

2-D Ramjet Inlet Example (cont'd)

- Compute efficiency Oblique shock inlet




- Compute T_C , T_B

$$T_{\underline{C}} = \frac{909.93}{\left(1 + \frac{1.4 - 1}{2} 0.557853^2\right)} = 856.61^\circ\text{K}$$

$$T_{\underline{B}} = \frac{1407.6}{\left(1 + \frac{1.4 - 1}{2} 0.557853^2\right)} = 1325.1^\circ\text{K}$$

2-D Ramjet Inlet Example (cont'd)

- Compute efficiency Oblique shock inlet



- Compute T_C , T_B

$$T_{C_B} = 856.61^\circ\text{K}$$


$$T_{B_C} = 1325.1^\circ\text{K}$$

$$\eta = 1 - \frac{\left(\frac{P_A}{P_B}\right)^{\frac{\gamma-1}{\gamma}} \left(T_C - \left(\frac{P_{0B}}{P_{0A}}\right)^{\frac{\gamma-1}{\gamma}} T_B \right)}{(T_C - T_B)} =$$

$$1 - \frac{38.422^{\frac{-(1.4-1)}{1.4}} \left(1325.1 - \left(0.3126^{\frac{(1.4-1)}{1.4}} \right) 856.61 \right)}{(1325.1 - 856.61)} = 0.4652$$


2-D Ramjet Inlet Example (cont'd)

- Compute efficiency Oblique shock inlet





Supersonic Inlet: Concorde Inlet Design

Concorde
Technical Specs



- Mach 2 Cruise



Credit:
<http://www.concordesst.com/powerplant.html>

Conical versus 2-D Inlets



SR-71



Concorde



X-15 Ramjet



F-15

“Starting” a Constant Geometry Ramjet Inlet






FIG. 5.33. Overspeed starting of fixed-geometry supersonic inlet, designed for free-stream Mach Number M_{∞} , and having contraction ratio $(A_2/A_1)_c$.

Air to Fuel Ratio Computations



- Stagnation enthalpy of the air and burned products leaving the combustor equals the enthalpy of the air entering the combustor + heat released by chemical reaction
- Sensible enthalpy of fuel assumed to be negligible when compared to heat of reaction

Fuel to Air Ratio Computations (cont'd)



$$\dot{m}_{air} (1 + f) C_{p_3} T_{0_3} = \dot{m}_{air} C_{p_2} T_{0_2} + \dot{m}_f q_r$$

$$= \dot{m}_{air} C_{p_2} T_{0_2} + f \dot{m}_{air} q_r$$

Solve for f

$$f = \frac{C_{p_3} T_{0_3} - C_{p_2} T_{0_2}}{(q_r - C_{p_3} T_{0_3})} = \frac{\frac{C_{p_3} T_{0_3}}{C_{p_2} T_{0_2}} - 1}{\left(\frac{q_r}{C_{p_2} T_{0_2}} - \frac{C_{p_3} T_{0_3}}{C_{p_2} T_{0_2}} \right)}$$

T_{0_2} -- stagnation temperature
entering burner

T_{0_3} -- stagnation temperature
exiting burner

f -- fuel to air ratio


C_{p_2} -- specific heat of
air entering burner

C_{p_3} -- specific heat of
combustion products

q_r -- heat of reaction

Equivalence Ratio versus Mixture Ratio

- The equivalence ratio is used to characterize the mixture ratio
Of airbreathing engines ... *analogous to mixture ratio*
- The *equivalence ratio*, Φ , is defined as the ratio of the actual fuel-air ratio to the stoichiometric fuel-air ratio.


 ... $\Phi > 1$ ---> a rich mixture
 ... $\Phi < 1$ ---> lean mixture


- For $\Phi = 1$, no oxygen is left in exhaust products ... combustion is called *stoichiometric*

$$\Phi \equiv \frac{\left[\frac{\dot{m}_{fuel}}{\dot{m}_{air}} \right]_{actual}}{\left[\frac{\dot{m}_{fuel}}{\dot{m}_{air}} \right]_{stoich}} = \frac{[f]_{actual}}{[f]_{stoich}}$$

Equivalence Ratio versus Mixture Ratio

(cont'd)

- Consider combustion of H_2 fuel with air ... what is Stoich fuel ratio
(define only water as product of combustion)



$$\left(\frac{\dot{m}_{H_2}}{\dot{m}_{O_2}} \right)_{stoich} = \frac{2 \frac{kg}{kg-mol} \times 2_{kg-mol}}{32 \frac{kg}{kg-mol} \times 1_{kg-mol}} = \frac{1}{8} \rightarrow (f)_{stoich} = \left(\frac{\dot{m}_{H_2}}{\dot{m}_{air}} \right)_{stoich} = \left(\frac{\dot{m}_{H_2}}{\dot{m}_{O_2}} \right)_{stoich} \times \frac{0.21 \dot{m}_{O_2}}{\dot{m}_{air}} = 0.02625$$

Air/Fuel=38.09

- Assumed equilibrium chemistry is described by reaction above with only water vapor as combustion product, + left over atmospheric nitrogen

Let's do the real flame temperature calculation

CEA Calculation

- Actual Equilibrium Calculations, Gaseous H_2 , air, $\phi=1$, $p_c=1000$ kPa (145 psi)
TB=856.6 °K (earlier ramjet problem)(After compression)_

Assumed air composition (dry air)

Nitrogen	79.00
Oxygen	21.00

Frozen Flow Calculation

Combustion properties

	Burner	M=1
T, K	2826.42	2521.42
H, KJ/KG	785.57	260.70
U, KJ/KG	-160.58	-583.35
G, KJ/KG	-28431.7	-25803.7
M, (1/n)	24.838	24.838
GAMMA _s	1.2395	1.2437

O/F= 38.09

Combustion Product MOLE FRACTIONS

	Burner	M=1
H ₂ O	0.31761	0.31761
N ₂	0.68239	0.68239

CEA Calculation, more realistic reaction

- Actual Equilibrium Calculations, Gaseous H_2 , air, $\phi=1$, $p_c=1000$ kPa (145 psi)
TB=856.6 °K (earlier ramjet problem) (After compression)

Gas % of Earth Atmosphere at sea level (dry air)

Nitrogen	78.08	
Oxygen	20.95	Equilibrium reactions
Argon	0.94	Reduces flame temperature
Carbon dioxide	0.03	Compared to previous

Equilibrium Flow Calculation

Combustion properties

	Burner	M=1
T, K	2662.82	2446.29
H, KJ/KG	779.69	288.07
U, KJ/KG	-120.74	-534.64
G, KJ/KG	-26714.1	-24970.0
M, (1/n)	24.588	24.723
GAMMA _s	1.1814	1.1951
O/F=	37.88393	

Combustion Product MOLE FRACTIONS

	Burner	M=1
Ar	0.00564	0.00567
CO	0.00005	0.00003
CO ₂	0.00012	0.00014
H	0.00205	0.00086
H ₂	0.01718	0.01062
H ₂ O	0.29080	0.30174
NO	0.00402	0.00229
N ₂	0.66569	0.67022
O	0.00065	0.00025
OH	0.00936	0.00523
O ₂	0.00445	0.00296

CEA Calculations (cont'd)

- Actual Equilibrium Calculations, Gaseous H_2 , air, $\phi=2$, $p_c=1000$ kPa (145 psi)
TB=856.6 °K (earlier ramjet problem) **(rich mixture)**

Gas % of Earth Atmosphere at sea level (dry air)

Nitrogen	78.08
Oxygen	20.95
Argon	0.94
Carbon dioxide	0.03

**Reduced flame temperature
Compared to previous
But molecular weight is lower**

Combustion properties




	Burner	M=1
T, K	2422.36	2156.10
H, KJ/KG	963.90	382.97
U, KJ/KG	-76.701	-542.18
G, KJ/KG	-28674.1	-25997.3
M, (1/n)	19.355	19.377
GAMMA _s	1.2399	1.2559

O/F= 37.88393

Combustion Product MOLE FRACTIONS


	Burner	M=1
Ar	0.00433	0.00433
CO	0.00011	0.00010
CO ₂	0.00002	0.00002
H	0.00274	0.00091
H ₂	0.23958	0.24051
H ₂ O	0.24021	0.24097
NH ₃	0.00001	0.00001
NO	0.00004	0.00001
N ₂	0.51239	0.51300
OH	0.00057	0.00013

CEA Calculations (cont'd)



Specific Thrust of Air Breathing Engine

- Analogous to specific impulse



$$Thrust = \dot{m}_e V_e - \dot{m}_i V_i + (p_e A_e - p_\infty A_e)$$

Cruise design condition
When $p_e = p_\infty$

$$\left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = \frac{[\dot{m}_f + \dot{m}_{air}] V_e - \dot{m}_{air} V_\infty}{\dot{m}_f} = \left[1 + \frac{1}{f} \right] V_e - \frac{1}{f} V_\infty = V_e + \frac{1}{f} (V_e - V_\infty)$$

Specific Thrust of Air Breathing Engine (cont'd)

- Re writing in terms of mach number

$$\begin{aligned} \left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} &= \left(\frac{f+1}{f} \right) V_e - \frac{1}{f} V_\infty = \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_e} M_e - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_\infty} M_\infty \right) = \\ & \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_{o_e}} \sqrt{\frac{T_e}{T_{o_e}}} M_e - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_{0_\infty}} \sqrt{\frac{T_\infty}{T_{0_\infty}}} M_\infty \right) = \\ & \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_{o_e}} \frac{M_e}{\sqrt{1 + \frac{\gamma_e - 1}{2} M_e^2}} - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_{0_\infty}} \frac{M_\infty}{\sqrt{1 + \frac{\gamma_\infty - 1}{2} M_\infty^2}} \right) \end{aligned}$$

Specific Thrust of Air Breathing Engine (cont'd)

- Re writing in terms of mach number

$$\left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_{o_e}} \frac{M_e}{\sqrt{1 + \frac{\gamma_e - 1}{2} M_e^2}} - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_{0_\infty}} \frac{M_\infty}{\sqrt{1 + \frac{\gamma_\infty - 1}{2} M_\infty^2}} \right)$$


Function of combustion

Function of Nozzle geometry

$$f = \Phi f_{stoich}$$

- Equivalence ratio, engine pressure ratio, nozzle drive process

Revisit Earlier Ramjet problem



- Compute Specific Thrust for $\Phi=1$, gaseous H_2 fuel
- Nozzle Optimized for operation at ~ 10 km altitude ($p_\infty = p_e = 26.43$ kPa) ... $p_{\text{burner}} \sim 1015.5$ kPa
- Assume frozen chemistry at burner


$$M_B = 0.557853$$

$$\frac{P_{0_B}}{P_{0_\infty}} = 0.3126$$

$$\frac{p_B}{P_{0_\infty}} = 38.422$$

Revisit Earlier Ramjet problem (cont'd)

= 1253 kPa



- Calculate exit stagnation pressure:

$$P_{0_\infty} = 26.4 \left(1 + \frac{1.4 - 1}{2} 4^2 \right)^{\left(\frac{1.4}{1.4 - 1} \right)} = 4008.5 \text{ kPa}$$


$$P_{0_e} = 0.3126 \left(26.4 \left(1 + \frac{1.4 - 1}{2} 4^2 \right)^{\left(\frac{1.4}{1.4 - 1} \right)} \right) = 1253.0 \text{ kPa}$$

$$M_B = 0.557853$$

$$\frac{P_{0_B}}{P_{0_\infty}} = 0.3126$$

$$\frac{p_B}{P_{0_\infty}} = 38.422$$

Revisit Earlier Ramjet problem (cont'd)



From earlier CEA calculations

$\gamma_e \sim 1.1814 \rightarrow \Phi=1$, gaseous H_2 fuel,


$p_{\text{burner}} \sim 1000 \text{ kPa}$

$$M_e = \sqrt{\frac{2}{\gamma_e - 1} \left[\left(\frac{P_{0_e}}{p_e} \right)^{\frac{\gamma_e - 1}{\gamma_e}} - 1 \right]}$$


- Calculate exit M_e

$$\left(\frac{2}{1.1814 - 1} \left(\left(\frac{1253}{26.4} \right)^{\frac{1.1814 - 1}{1.1814}} - 1 \right) \right)^{0.5} = 2.986$$

$$A_e/A^* = 7$$



Revisit Earlier Ramjet problem (cont'd)




- Assume $A_e/A^* = 7.0$
- Compute free stream stagnation temperature

$$T_{0_\infty} = T_\infty \left[1 + \frac{\gamma - 1}{2} M_\infty^2 \right] = 216.65 \left(1 + \frac{1.4 - 1}{2} 4^2 \right) = 909.93^\circ\text{K}$$

Revisit Earlier Ramjet problem (cont'd)

- Exit stagnation temperature ... From earlier CEA calculations



$$T_{\text{burner}} = 2662.82 \text{ }^{\circ}\text{K}$$

- From inlet earlier problem

$$M_B = 0.557853$$

$$\frac{P_{0_B}}{P_{0_{\infty}}} = 0.3126$$

$$\frac{p_B}{P_{0_{\infty}}} = 38.422$$

$$T_{0_{\text{burner}}} =$$

$$2662.82 \left(1 + \frac{1.1814 - 1}{2} 0.55785^2 \right) = 2738.2 \text{ }^{\circ}\text{K}$$


Revisit Earlier Ramjet problem (cont'd)

- Calculate specific thrust

$$\left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_{o_e}} \frac{M_e}{\sqrt{1 + \frac{\gamma_e - 1}{2} M_e^2}} - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_{0_\infty}} \frac{M_\infty}{\sqrt{1 + \frac{\gamma_\infty - 1}{2} M_\infty^2}} \right)$$

$$f = \Phi f_{stoich} = (1) \frac{1}{37.88393} = 0.0265$$

$$M_W = 24.6 \rightarrow R_g = 337.98 \text{ J/kg-degK}$$



Revisit Earlier Ramjet problem (cont'd)

- Calculate specific thrust

$$\left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = \left(\frac{f+1}{f} \right) \sqrt{\gamma_e R_{g_e} T_{o_e}} \frac{M_e}{\sqrt{1 + \frac{\gamma_e - 1}{2} M_e^2}} - \frac{1}{f} \left(\sqrt{\gamma_\infty R_{g_\infty} T_{0_\infty}} \frac{M_\infty}{\sqrt{1 + \frac{\gamma_\infty - 1}{2} M_\infty^2}} \right)$$

$$\left(\frac{0.0265 + 1}{0.0265} \right) (1.1814 \cdot 337.98 \cdot 2738.2)^{0.5} \frac{(2.986)}{\left(1 + \frac{1.1814 - 1}{2} (2.986)^2 \right)^{0.5}} -$$

$$\left(\frac{1}{0.0265} \right) (1.4 \cdot 287 \cdot 909.93)^{0.5} \frac{4}{\left(1 + \frac{1.4 - 1}{2} (4)^2 \right)^{0.5}} = 45397 \text{ Nt/kg/sec}$$

... convert to seconds $\frac{1}{g_0} \left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = \frac{89928.2835 - 44534.69}{9.8077} = 4628.4 \text{ sec}$


Wow!

Revisit Earlier Ramjet problem (cont'd)

- Calculate specific thrust

$$\frac{1}{g_0} \left(\frac{F_{thrust}}{\dot{m}_f} \right)_{opt} = 4628.4 \text{ sec}$$

- Idealized analysis ... with a 2-D inlet
- If we consider losses of 10% then we are right in the middle of the predicted operating range



What is the thermodynamic efficiency

$$\eta = 1 - \left(\frac{P_A}{P_B} \right)^{\frac{\gamma-1}{\gamma}} \frac{\left(T_C - \left(\frac{P_{0_B}}{P_{0_A}} \right)^{\frac{\gamma-1}{\gamma}} T_B \right)}{(T_C - T_B)} =$$

$$1 - \frac{38.422^{\frac{-(1.4-1)}{1.4}} \left(2662.82 - \left(0.3126^{\frac{(1.4-1)}{1.4}} \right) 856.61 \right)}{(2662.82 - 856.61)} = 0.600 \quad \text{Not Bad!}$$